

AUTOMATIC INFLATORS STANDARD CABINETS

PCL'S line of Standard Air and Standard Air & Water Cabinets provide an attractive and stylish appearance while meeting the demands of auto service centers. All components of these systems are built for ease of use, reliability, and extended life.



STANDARD AIR CABINET

SPECIFICATIONS

Compliance:	EC Directive 86/217 and BS EN 12645:2014
Reading Accuracy:	1 psi
Max. Supply Pressure:	232 psi
Inflation Flow:	14 cfm
Inflation Range:	0-145 psi
Operating Temperature:	-4°F to 158°F
IP Rating:	IP44

KEY BENEFITS

- New high performance, slow retractable hose reels as standard
- Alternative tire valve connectors available for all units

PART # DESCRIPTION

D95SS20C/0004	STANDARD CABINET, 25' AIR HOSE REEL W/ CLIP-ON CONNECTOR, & WATER HOSE
D97SS20C/0004	STANDARD CABINET, 25' AIR HOSE REEL W/ CLIP-ON CONNECTOR, 145 PSI COMPRESSOR

SPECIFICATIONS

Compliance:	EC Directive 86/217 and BS EN 12645:2014
Reading Accuracy:	1 psi
Max. Supply Pressure:	232 psi
Inflation Flow:	14 cfm
Inflation Range:	0-145 psi
Operating Temperature:	-4°F to 158°F
IP Rating:	IP44

KEY BENEFITS

- New high performance, slow retractable hose reels as standard
- Alternative tire valve connectors available for all units

PART # DESCRIPTION

D96SS20C/0004	STANDARD CABINET, 25' AIR HOSE REEL W/ CLIP-ON CONNECTOR, 12' WATER HOSE REEL, NO COMPRESSOR
D98SS20C/0004	STANDARD CABINET, 25' AIR HOSE REEL W/ CLIP-ON CONNECTOR, 12' WATER HOSE REEL, 145 PSI COMPRESSOR



STANDARD AIR & WATER CABINET