

# AUTOMATIC INFLATORS WALL MOUNTED



**ACCURA® D10**

## SPECIFICATIONS

Compliance:	EC Directive 86/217 & BS EN 12645:2014
Reading Accuracy:	1 psi
Maximum Supply Pressure:	232 psi
Inflation Flow:	14 cfm
Inflation Range:	0-145 psi
Operating Temperature:	-4°F to 158°F
Dimensions:	12" x 17" x 4"
IP Rating:	IP66

## APPROVALS

German:	PTB 18.08/04.01 (Single and Dual Screen)
French:	F-06-H-157 (Dual Screen)
Portuguese:	245.30.04.3.14 (Single Screen)
Spanish:	111063001 (Single Screen)

## ACCURA® D10 TIRE INFLATOR

PCL's ACCURA® D10 Tire Inflator includes trusted, reliable "menu-driven" units found in tire shops throughout the world.

Suitable for tire service centers, the electronic preset units capture new digital technology in a modern, aesthetic design, offering repetitive accuracy, reduced maintenance, and limited lifestyle costs.

The easy-to-use ACCURA® D10 Tire Inflator includes a wall-mounted range and pedestal unit, as well as a self-contained unit with retractable air and water reels - suitable for indoor or outdoor use.

All use auto-start inflation and a "default to safe" setting. These units provide the user with greater safety, increased fuel economy, and extended tire life.

## KEY BENEFITS

- Plug and play - tire inflator with 3 pre-selectable modes
- Extended product life with robust design and proven electronics
- Low and simple maintenance with excellent diagnostics
- Individually tested calibration certificate included
- Electronic pressure preset
- Auto-start inflation
- Default to safe-setting
- Reliable and modern design with die-cast aluminum housing
- Ceramic sensor
- Accurately inflates using hoses up to 164 ft.
- Comprehensive diagnostics and error reporting
- Wall or pedestal mounting
- Increased safety and reduced tire-related incidents
- Indoor/outdoor use

PART #	DESCRIPTION
<b>D10SS20T/0004</b>	D10 TIRE INFLATOR WALL MOUNTED FUELING STATION SPO