

# HANDHELD INFLATORS DIGITAL

PCL's line of digital handheld tire inflators are a very useful addition to any professional workshop. The ACCURA® 1 breaks the tradition for handheld units, combining ease of use and readability, with rapid and safe tire inflation. The DTI tire inflator is highly accurate and suitable for all kinds of tire applications.

<b>DAC1ACH2</b>	21" HOSE, STRAIGHT SINGLE 1/4" FBSP
<b>DAC1ACH4</b>	21" HOSE, ANGLED SINGLE 1/4" FBSP
<b>DAC1A6CH2</b>	6' HOSE, STRAIGHT SINGLE 1/4" FBSP
<b>DAC1A6CH4</b>	6' HOSE, ANGLED SINGLE 1/4" FBSP

\*ACCURA 1 WITH NEW PRO-CONNECT CHUCK SHOWN BELOW



STANDARD CHUCK



BRASS  
INLET

NEW PRO-CONNECT  
ZERO-AIR-LOSS CHUCK

COMPLETE WITH  
CALIBRATION  
CERTIFICATE

## ACCURA® 1 TIRE INFLATOR

### SPECIFICATIONS

Compliance:	EC Directive 86/217 & CARB Compliant
Reading Accuracy:	0.2 psi
Max. Supply Pressure:	218 psi
Inflation Flow:	32 cfm@188 psi
Inflation Range:	0-174 psi

### KEY BENEFITS

- Inflate/deflate tire pressure while engaged on tire valve system
- Individually tested calibration certificate included
- Robust, lightweight, and shock resistant construction
- Over-pressure warning if pressure exceeds 174 psi

### PART # DESCRIPTION

<b>DAC1A031</b>	21" HO , TWIN ANGLED CHUCK WITH BRASS INLET
<b>DAC1A08N</b>	6' HOSE, SINGLE LOCK ON CHUCK WITH BRASS INLET
<b>DAC1A081N</b>	21" HOSE, SINGLE LOCK ON CHUCK WITH BRASS INLET

### SPECIFICATIONS

Compliance:	EC Directive 86/217 & CARB Compliant
Reading Accuracy	1 psi
Max. Supply Pressure:	218 psi
Inflation Flow:	32 cfm
Inflation Range:	5-170 psi

### KEY BENEFITS

- Inflate/deflate tire pressure while engaged on tire valve system
- Individually tested calibration certificate included
- Large, clear, easy to read LCD display with backlight
- Psi, bar, kPa units of pressure selectable by button
- Guaranteed accuracy

### PART # DESCRIPTION

<b>DTI08N</b>	6' HOSE, SINGLE LOCK ON CHUCK WITH BRASS INLET
<b>DTI081N</b>	21" HOSE, SINGLE LOCK ON CHUCK WITH BRASS INLET

<b>DTI0CH2</b>	21" HOSE, STRAIGHT SINGLE 1/4" FBSP
<b>DTI0CH4</b>	21" HOSE, ANGLED SINGLE 1/4" FBSP
<b>DTI06CH2</b>	6' HOSE, STRAIGHT SINGLE 1/4" FBSP
<b>DTI06CH4</b>	6' HOSE, ANGLED SINGLE 1/4" FBSP

\*DTI WITH NEW PRO-CONNECT CHUCK SHOWN BELOW



STANDARD CHUCK



NEW PRO-CONNECT  
ZERO-AIR-LOSS CHUCK

COMPLETE  
WITH  
CALIBRATION CERTIFICATE

BRASS  
INLET

## DTI TIRE INFLATOR